

类似效果实例

```
#include "Swing.au3"
```

```
#include <Excel.au3>
```

```
#include <Array.au3>
```

```
shellexecute("C:\Users\Admin\AppData\Local\UClient\apps\121c9f01-b00e-366b-ae6b-52e4cdd0d056\Launcher.exe", "121c9f01-b00e-366b-ae6b-52e4cdd0d056")
```

```
Sleep(5000)
```

```
Opt("MouseCoordMode", 0)
```

```
Opt("SendKeyDelay", 20)
```

```
global $wintitle = "Yonyou NC - nc65:8080"
```

```
$winHandle = WinActivate($wintitle)
```

```
WinSetState($wintitle, "", @SW_MAXIMIZE)
```

```
$result = __isJavaWindow($winHandle)
```

```
Global $vmId
```

```
Global $ac
```

```
global $sName = "用户"
```

```
global $sRole = "label"
```

```
__getAccessibleContextFromHWND($winHandle, $vmID, $ac)
```

Sleep(500)

\$re_ac = _JAB_getAccessibleContextByFindAll(\$vmId, \$ac, \$sName, \$sRole)

_JAB_getIndexInParent(\$vmId, \$re_ac)

\$indexObject = __getAccessibleParentFromContext(\$vmId, \$re_ac)

\$username = __getAccessibleChildFromContext(\$vmId, \$indexObject, 3)

\$passwd = __getAccessibleChildFromContext(\$vmId, \$indexObject, 5)

\$loginBtn = __getAccessibleChildFromContext(\$vmId, \$indexObject, 7)

__setTextContents(\$vmId, \$username, "slwql")

__setTextContents(\$vmId, \$passwd, "@365")

_JAB_singleAction(\$vmId, \$loginBtn)

Sleep(600)

If WinExists("提示") Then

\$hWnd=WinGetHandle("[ACTIVE]");

\$ret=DllCall("user32.dll","long","LoadKeyboardLayout","str","08040804","int",1+0);

DllCall("user32.dll","ptr","SendMessage","hwnd",\$hWnd,"int",0x50,"int",1,"int",\$ret[0]);

Sleep(400)

WinActivate("提示")

Sleep(400)

Send("{Y}")

Sleep(400)

EndIf

Sleep(200)

\$function_ac = _JAB_getAccessibleContextByFindAll(\$vmId, \$ac, "财务会计",
"page tab")

Sleep(200)

Send("{DOWN 5}")

Sleep(200)

\$base_ac = _JAB_getAccessibleContextByFindAll(\$vmId, \$ac,
"基础档案及规则", "label")

Sleep(200)

\$indexList = __getAccessibleParentFromContext(\$vmId, \$base_ac)

Sleep(200)

\$clickLabel = __getAccessibleChildFromContext(\$vmId, \$indexList, 1)

Sleep(200)

_JAB_singleAction(\$vmId, \$clickLabel)

Sleep(300)

\$infoX = _JAB_getX(\$vmId, \$clickLabel)

\$infoY = _JAB_getY(\$vmId, \$clickLabel)

Sleep(20)

\$posx = \$infoX + 280

Sleep(20)

\$posy = \$infoY + 20

Sleep(20)

MouseClick("left", \$posx, \$posy, 1)

Sleep(200)

Send("{DOWN 10}")

Sleep(200)

Send("{ENTER}")

Sleep(100)

\$searchBtn = _JAB_getAccessibleContextByFindAll(\$vmId, \$ac, "查询", "push button")

Sleep(100)

Send("{F3}")

Sleep(600)

If WinExists("凭证查询") Then

\$searchDialog = WinActivate("凭证查询")

Sleep(200)

\$result = __isJavaWindow(\$searchDialog)

__getAccessibleContextFromHWND(\$searchDialog, \$vmId, \$ac)

Sleep(100)

```
$accountLabel = _JAB_getAccessibleContextByFindAll($vmId, $ac,  
"核算账簿", "label")
```

```
Sleep(40)
```

```
$accoutBtn = _JAB_getNextSibling($vmId, $accountLabel, 1)
```

```
Sleep(40)
```

```
$btn = __getAccessibleChildFromContext($vmId, $accoutBtn, 1)
```

```
Sleep(40)
```

```
_JAB_singleAction($vmId, $btn)
```

```
Sleep(100)
```

```
Send("{DOWN 2}")
```

```
Sleep(40)
```

```
Send("{RIGHT}")
```

```
Sleep(40)
```

```
Send("{DOWN}")
```

```
Sleep(40)
```

```
Send("{ENTER}")
```

```
Sleep(40)
```

```
$confirmBtn = _JAB_getAccessibleContextByFindAll($vmId, $ac, "确定",  
"push button")
```

```
Sleep(40)
```

```
_JAB_singleAction($vmId, $confirmBtn)
```

Sleep(600)

WinFlash("凭证查询")

EndIf

Sleep(100)

Send("{TAB 2}")

Sleep(100)

\$result = __isJavaWindow(\$winHandle)

Sleep(40)

__getAccessibleContextFromHWND(\$winHandle, \$vmId, \$ac)

Sleep(40)

\$page_tab = _JAB_getAccessibleContextByFindAll(\$vmId, \$ac, "查询", "page
tab")

Sleep(40)

\$table_header = _JAB_getAccessibleContextByFindAll(\$vmId, \$page_tab,
"出纳", "label")

Sleep(40)

\$table = _JAB_getTableFromColumn(\$vmId, \$table_header)

Sleep(40)

\$count = _JAB_getTableRowCount(\$vmId, \$table)

Sleep(300)

Send("{DOWN 20}")

Sleep(200)

\$cardBtn = _JAB_getAccessibleContextByFindAll(\$vmId, \$page_tab, "卡片显示", "push button")

Sleep(200)

_JAB_singleAction(\$vmId, \$cardBtn)

Sleep(400)

Send("{TAB 1}")

Sleep(400)

\$backBtn = _JAB_getAccessibleContextByFindAll(\$vmId, \$page_tab, "返回", "push button")

Sleep(400)

MouseMove(16, 249, 10)

Sleep(40)

__getAccessibleContextWithFocus(\$winHandle, \$vmId, \$ac)

Sleep(40)

\$iTableHeadCount = _JAB_getTableColumnCount(\$vmId, \$ac)

\$iTableRowCount = _JAB_getTableRowCount(\$vmId, \$ac)

Sleep(400)

Local \$oExcel = _Excel_Open()

Local \$sFilePath = "D:\test.xls"

Local \$oWorkbook = _Excel_BookOpen(\$oExcel, \$sFilePath)

```
Local $oSheet = $oWorkbook.Sheets(1)
```

```
Sleep(400)
```

```
;Local $tableHeads[12] = ["分录号", "摘要", "科目", "辅助核算", "币种", "原币",  
"组织本币 (借方)", "组织本币 (贷方)", "集团本币 (借方)",  
"集团本币 (贷方)", "全局本币 (借方)", "全局本币 (贷方)"]
```

```
;$file = FileOpen("C:\data.txt", 1)
```

```
For $i = 0 To $iTableRowCount - 1
```

```
Local $tableData[12]
```

```
For $j = 0 To $iTableHeadCount - 1
```

```
Local $tableCell = _JAB_getTableCellTextValue($vmId, $ac, $i, $j)
```

```
Local $cellValue = StringRegExpReplace($tableCell, '<[/!]*?[^<>]*?>', '')
```

```
Sleep(20)
```

```
;$_ArrayAdd($tableData, $tableCell)
```

```
$oSheet.Range("A2").Offset($i, $j).Value = $cellValue
```

```
$oSheet.Range("A:L").Columns.AutoFit
```

```
;FileWriteLine($file, $tableHeads[$j] & @TAB & ":" & $tableCell & @CRLF)
```

```
;If $j = 11 Then
```

```
; FileWriteLine($file, $tableCell & @CRLF & "=====  
=====")
```

```
;EndIf
```

```
Next
```


Next

Sleep(400)

_Excel_BookSave(\$oWorkbook)

Sleep(400)

_Excel_BookClose(\$oWorkbook)

_Excel_Close(\$oExcel)

;FileClose(\$file)

Sleep(400)

WinClose(\$wintitle)